



Dn5	Catalog No.	ØD	L	0.01 mm.					B	od	F
				(A)	(B)	(C)	(D)	(E)			
ชนิด (Type)				min. P	max.	P•Kmax.	P•Wmin.	R			
10	BSA-W	10	16 20 22 25 30 35	2.00	6.00	6.00	1.20	0.20 ≤ R < W/2 (E only)	6	6	
13		13	16 20 22 25 30 35	3.00	8.00	8.00	1.50		8.4	7.5	
16	BSB-W	16	16 20 22 25 30 35	5.00	10.00	10.00	2.00		10.6	8	
20		20	16 20 22 25 30 35	7.00	12.00	12.00	3.00		12.6	10	
25	BSC-W	25	16 20 22 25 30 35	10.00	16.00	16.00	3.00		16.6	12.5	
32		32	16 20 22 25 30 35	15.00	20.00	20.00	4.00		20.6	16	
38	BSD-W	38	16 20 22 25 30 35	19.00	26.00	26.00	5.00		26.6	19	
45		45	20 22 25 30 35	25.00	35.00	35.00	6.00		36.0	22.5	
50	BSE-W	50	20 22 25 30 35	33.00	40.00	40.00	7.00		41.0	25	
56		56	20 22 25 30 35	38.00	45.00	45.00	8.00		46.0	28	

Order Catalog No. ØD - L - P - W - R (E only)

BSE-W 13 - 20 - P6.00 - W2.40 - R1.00

ราคา บาท/ชิ้น (Baht/Piece)

ØD	BSA-W	BSB-W BSC-W BSD-W BSE-W
10	251	850
13	230	884
16	230	934
20	251	986
25	315	1,054
32	389	1,110
38	704	1,568
45	1,529	3,146
50	1,837	3,531
56	2,244	3,933

ลักษณะการเปลี่ยนแปลง (Alterations)	Code การสั่ง	(A) (โตนง)	(B) (โตนงหัว)	(C) (โตนงหัว)	(D) (โตนงหัว)	(E) (โตนงหัว)	จำนวนชิ้น (บาท) (Baht/Piece)
เปลี่ยนขนาดโตนง	PC WC	min : P > PC ≥ P•Wmin. / 2 W WC	max : P < PC ≤ P•Kmax. + 0.2 W WC	0.01mm.	0.01mm.		40
เปลี่ยนความยาวโตนง	LC	10 ≤ LC < L	0.1mm.				40
เปลี่ยนขนาดรู	KC		270° 180° 0° 90°	1°			40
เปลี่ยน P โตนงหัว	PKC	P+0.01 ⇔ +0.005 0 0	P•W 0.01 ⇔ +0.01 0 0				80
เปลี่ยนความยาวโตนงหัว	LKC	L+0.4 ⇔ +0.05 +0.2 0					80